




CLI-RBC 型为交叉滚子轴承的外圈被分为两片，内圈为整体结构，它适用于要求内圈旋转精度的场合。CLI-RBC 型在 CLI-RB 型基础上内置钢制保持架，适用于工作温度稍高且要求转速的场合，一般为开式结构。可以完美替代 IKO 公司的 CRBC 系列轴承。
 * CLI-RBC crossed roller bearing has separable outer ring while the inner ring is integrated with the main body. CLI-RBC bearing is used in locations where the rotation accuracy of the inner ring is required. Major applications include the index table swiveling unit of machine tools. It is the best alternative of IKO's CRBC bearings.




CLI Part NO.	Boundary Dimensions (mm)			Roller Diameter (mm)	Shoulder Dimensions (mm)			Rated Loading		Weight	Cross Reference
	ID (d)	OD (D)	W (B)	Dp w	ds	Dh	C	Co	(kg)	IKO	
CLI-RBC 3010	30	55	10	39	34	44	7.35	8.36	0.12	CRBC3010	
CLI-RBC 4010	40	65	10	49	44	54	8.33	10.6	0.15	CRBC4010	
CLI-RBC 5013	50	80	13	63	55	71	16.7	20.9	0.29	CRBC5013	
CLI-RBC 6013	60	90	13	72.5	64	81	18	24.3	0.33	CRBC6013	
CLI-RBC 7013	70	100	13	83	75	91	19.4	27.7	0.35	CRBC7013	
CLI-RBC 8016	80	120	16	96.5	86	107	30.1	42.1	0.74	CRBC8016	
CLI-RBC 9016	90	130	16	108	98	118	31.4	45.3	0.81	CRBC9016	
CLI-RBC 10020	100	150	20	121	108	134	33.1	50.9	1.45	CRBC10020	
CLI-RBC 11020	110	160	20	131	118	144	34	54	1.56	CRBC11020	
CLI-RBC 12025	120	180	25	148	132	164	66.9	100	2.62	CRBC12025	
CLI-RBC 13025	130	190	25	156	140	172	69.5	107	2.82	CRBC13025	
CLI-RBC 14025	140	200	25	167	151	183	74.8	121	2.96	CRBC14025	
CLI-RBC 15025	150	210	25	176	160	192	76.8	128	3.16	CRBC15025	
CLI-RBC 15030	150	230	30	134	166	202	100	156	5.3	CRBC15030	
CLI-RBC 20025	200	260	25	223.5	208	239	84.2	157	4	CRBC20025	
CLI-RBC 20030	200	280	30	240	218	262	114	200	6.7	CRBC20030	
CLI-RBC 20035	200	295	35	247.5	221	274	151	252	9.6	CRBC20035	
CLI-RBC 25025	250	310	25	274.5	259	290	69.3	150	5	CRBC25025	
CLI-RBC 25030	250	330	30	287.5	265	310	126	244	8.1	CRBC25030	

*** NOTES: ① Bearings with seals are CLI-RBC...UU; ② Please select inner ring's rotation way when needs higher precision bearings.



CLI-RBC 型为交叉滚子轴承的外圈被分为两片，内圈为整体结构，它适用于要求内圈旋转精度的场合。CLI-RBC 型在 CLI-RB 型基础上内置钢制保持器，适用于工作温度稍高且要求转速的场合，一般为开式结构。可以完美替代 IKO 公司的 CRBC 系列轴承。
 * CLI-RB crossed roller bearing has separable outer ring while the inner ring is integrated with the main body. CLI-RBC bearing is used in locations where the rotation accuracy of the inner ring is required. Major applications include the index table swiveling unit of machine tools. It is the best alternative of IKO's CRBC bearings.



CLI Part NO.	Boundary Dimensions (mm)			Roller Diameter (mm)		Shoulder Dimensions (mm)		Rated Loading		Weight (kg)	Cross Reference IKO
	ID (d)	OD (D)	W (B)	Dp w	ds	Dh	C	Co			
CLI-RBC 25040	250	355	40	300.5	271	330	195	348	14.8	CRBC25040	
CLI-RBC 30025	300	360	25	325.5	310	341	76.3	178	5.9	CRBC30025	
CLI-RBC 30035	300	395	35	345	318	372	183	367	13.4	CRBC30035	
CLI-RBC 30040	300	405	40	351	321	381	212	409	17.2	CRBC30040	
CLI-RBC 40035	400	480	35	435.5	414	457	156	370	14.5	CRBC40035	
CLI-RBC 40040	400	510	40	453	423	483	241	531	23.5	CRBC40040	
CLI-RBC 40070	400	590	70	481	430	532	470	811	72.4	CRBC40070	
CLI-RBC 50040	500	600	40	545	517	573	239	607	26	CRBC50040	
CLI-RBC 50050	500	625	50	561.5	531	592	267	653	41.7	CRBC50050	
CLI-RBC 50070	500	680	70	581.5	530	633	653	1330	86.1	CRBC50070	
CLI-RBC 60040	600	700	40	648.5	621	676	264	721	29	CRBC60040	
CLI-RBC 60070	600	780	70	682	630	734	700	1540	102	CRBC60070	
CLI-RBC 600120	600	870	120	730	643	817	1490	2800	274	CRBC600120	
CLI-RBC 70045	700	815	45	757.5	730	785	281	836	46	CRBC70045	
CLI-RBC 70070	700	880	70	782.5	731	734	766	1810	115	CRBC70070	
CLI-RBC 700150	700	1020	150	852	751	953	1980	3820	478	CRBC700150	
CLI-RBC 80070	800	950	70	869	831	907	468	1330	105	CRBC80070	
CLI-RBC 800100	800	1030	100	906	840	972	1140	2640	247	CRBC800100	

*** NOTES: ① Bearings with seals are CLI-RBC...UU; ② Please select inner ring's rotation way when needs higher precision bearings.