


CLI-RC



* CLI-RC 型 (内圈整体、外圈分体、超薄), 在相同的轴颈情况下, 此类型比 CLI-RB 类型有更小的截面尺寸, 由于采用了超薄设计, 外圈和内圈没有安装孔, 安装时需用法兰和支撑座固定, 适用于内圈旋转的应用场合。

* CLI-RC crossed roller bearings are bearings for high precision applications with super thin inner and outer rings, whose dimensions conform to ISO dimension series 18 to DIN 616. They comprise outer rings, inner rings, rolling elements and plastic spacers. The outer ring is split and is held together by three retaining rings. It is the best alternative of INA's SX bearings.



CLI Part NO.	Boundary Dimensions (mm)			Roller Diameter (mm)			Shoulder Dimensions (mm)			Rated Loading			Weight	Cross Reference
	ID (d)	OD (D)	W (B)	Dpw	ds	Dh	Ca	Coa	C	Co	(kg)	INA		
CLI-RC 7010	70	90	10	80	79.5	80.5	18	60	12	30	0.3	SX011814		
CLI-RC 9013	90	115	13	102	101.5	102.5	26	96	17	47	0.4	SX011818		
CLI-RC 10013	100	125	13	112	111.5	112.5	28	106	18	52	0.5	SX011820		
CLI-RC 12016	120	150	16	135	134.4	135.6	41	153	26	75	0.8	SX011824		
CLI-RC 14018	140	175	18	157	156.3	157.7	64	237	41	116	1.1	SX011828		
CLI-RC 16020	160	200	20	180	179.2	180.8	69	272	44	133	1.7	SX011832		
CLI-RC 18022	180	225	22	202	201.2	202.8	98	381	63	187	2.3	SX011836		
CLI-RC 20024	200	250	24	225	224.2	225.8	106	425	68	208	3.1	SX011840		
CLI-RC 24028	240	300	28	270	269.2	270.8	149	612	95	300	5.3	SX011848		
CLI-RC 30038	300	380	38	340	339.2	340.8	245	1027	156	504	12	SX011860		
CLI-RC 34038	340	420	38	380	379.2	380.8	265	1148	167	563	13.5	SX011868		
CLI-RC 40046	400	500	46	450	449	451	385	1699	244	833	24	SX011880		
CLI-RC 50056	500	620	56	560	558.8	561.2	560	2538	355	1244	44	SX0118/500		

*** NOTES: ① Bearings with seals are CLI-RC...UU; ② Please select inner ring's rotation way when needs higher precision bearings.