


CLI-RU



* CLI-RU 型 (内外圈整体、带安装孔), 由于带有安装孔, 安装时不需要固定法兰和支撑座。另外, 由于外圈和内圈均为整体结构, 安装时性能几乎没有影响, 因此能获得稳定的旋转精度和扭矩。适用于外圈和内圈旋转的场合。

* CLI-RU (Integrated Inner/Outer Ring Type) crossed roller bearing is providing with mounting holes. This model does not require a presser flange or housing. In addition, because it has an integrated inner/outer ring structure and is equipped with washers, its performance is minimally affected by the mounting procedure, ensuring stable rotation accuracy and torque. This model can be used for both inner-ring rotation and outer-ring rotation.



CLI Part NO.	Boundary Dimension (mm)				Bolt Hole Size for Installation (mm)				Rated Load (kN)		Weight (kg)	Cross Reference		
					Outer Ring		Inner Ring							
	ID (d)	OD (D)	W (B)	PCD	Bolt Hole Size		PCD	Bolt Hole Size		C	Co	THK	IKO	
CLI-RU1008	10	52	8	42			16	4-M3		2.91	2.43	0.1	-	CRBF108AT
CLI-RU2012	20	70	12	57	6-φ3.4 THRU, φ6.5 C'BORE x 3.3 DP		28	6-M3		7.35	8.35	0.3	RU42	CRBF2012AT
CLI-RU2512	25	80	12	67			35	6-M3		8.61	10.6	0.4	-	CRBF2512AT
CLI-RU3515	35	95	15	83	8-φ4.5 THRU, φ8 C'BORE x 4.4 DP		45	8-M4		17.5	22.3	0.7	RU66	CRBF3515AT
CLI-RU5515	55	120	15	105	8-φ5.5 THRU, φ9.5 C'BORE x 5.4 DP		65	8-M5		20.3	29.5	1.0	RU85	CRBF5515AT
CLI-RU8022	80	165	22	148	10-φ5.5 THRU, φ9.5 C'BORE x 5.4 DP	97	10-φ5.5 THRU, φ9.5 C'BORE x 5.4 DP		33.1	50.9	2.6	RU124	CRBF8022A	
CLI-RU8022G							10-M5					RU124G	CRBF8022AT	
CLI-RU8022X							12-M8					RU124X	CRBF8022AT	
CLI-RU9025	90	210	25	187	12-φ9 THRU, φ14 C'BORE x 8.6 DP	112	12-φ9 THRU, φ14 C'BORE x 8.6 DP		49.1	76.8	4.9	RU148	-	
CLI-RU9025G							12-M8					RU148G	-	
CLI-RU9025X							12-M8					RU148X	-	
CLI-RU11528	115	240	28	217	12-φ9 THRU, φ14 C'BORE x 8.6 DP	139	12-φ9 THRU, φ14 C'BORE x 8.6 DP		80.3	135	6.8	RU178	-	
CLI-RU11528G							12-M8					RU178G	-	
CLI-RU11528X							12-M8					RU178X	-	
CLI-RU16035	160	295	35	270	12-φ11 THRU, φ17.4 C'BORE x 10.8 DP	184	12-φ11 THRU, φ17.5 C'BORE x 10.8 DP		104	173	11.4	RU228	-	
CLI-RU16035G							12-M10					RU228G	-	
CLI-RU16035X							12-M10					RU228X	-	
CLI-RU21040	210	380	40	350	16-φ14 THRU, φ20 C'BORE x 13 DP	240	16-φ14 THRU, φ20 C'BORE x 13 DP		156	281	21.3	RU297	-	
CLI-RU21040G							16-M12					RU297G	-	
CLI-RU21040X							16-M12					RU297X	-	
CLI-RU35045	350	540	45	505	25-φ14 THRU, φ20 C'BORE x 13 DP	385	24-φ14 THRU, φ20 C'BORE x 13 DP		222	473	35.4	RU445	-	
CLI-RU35045G							24-M12					RU445G	-	
CLI-RU35045X							24-M12					RU445X	-	

*** NOTES: 1) Bearings with seals are CLI-RU...UU; 2) Please select inner ring's rotation way when needs higher precision bearings.