






- * CLI-RSU 系列交交滚了轴承(内圈外圈一体型; 内圈旋转/外圈旋转, 具有安装和和高铜性) 的结构与CLI-RU 轴承的结构 相同。更用了规模设计,但ECCT-PCO型具有更要基础是对外形和更高的边域速度。CLT-PSU带线:TNA公司的XSUOR系列 交叉溶子轴承:
- * CLI-RSU (One-piece Inner and Outer Ring) crossed roller bearing is providing with mounting holes. This model has the same structure of CLI-RU, but has tighter sizes and better working precision. CLI-RSU is the perfect alternative of INA's XSU08 series crossed roller bearings.



| CLI Part NO. | Boundary Dimensions (mm) | | | | Bolt Hole Dimensions (mm) | | | Rated Loading (KN) | | | | Weight | Cross Reference |
|---------------------------|--------------------------|-------------|--------------|-----------|---------------------------|-------------|-----------------|--------------------|--------------|--------------|-----------|--------|-----------------|
| | Da | di | Di | da | La | Li | nB1 | Ca | Coa | Cr | Cor | (kg) | INA |
| CLI-RSU168 | 205 | 130 | 174 | 159 | 190 | 145 | 12 | 65 | 243 | 41.4 | 119 | 3.3 | XSU080168 |
| CLI-RSU188 | 225 | 150 | 194 | 179 | 210 | 165 | 16 | 70 | 270 | 44.5 | 133 | 3.7 | XSU080188 |
| CLI-RSU218 | 255 | 180 | 224 | 209 | 240 | 195 | 20 | 76 | 315 | 48 | 154 | 4.3 | XSU080218 |
| CLI-RSU258 | 295 | 220 | 264 | 249 | 280 | 235 | 24 | 83 | 370 | 53 | 182 | 5.1 | XSU080258 |
| CLI-RSU318 | 355 | 280 | 324 | 309 | 340 | 295 | 28 | 94 | 465 | 60 | 228 | 6.3 | XSU080318 |
| CLI-RSU398 | 435 | 360 | 404 | 389 | 420 | 375 | 36 | 106 | 580 | 67 | 285 | 7.8 | XSU080398 |
| NOTES: 1) Bearing with ne | gative radial cl | earence Pre | loaded is Cl | J-RSUVSP; | 2) Please | select inne | r ring's rotati | on way whe | n needs high | er precision | bearings. | | |